

LED-LUC_60

Magnetic Spot »L«

GENERAL TECHNICAL SPECIFICATIONS



LED-Luc 60 | Little big one

Switch on the Spot! LED-Luc is small but powerful. To the point or for spacious illumination, as desired. In addition, it can be pivoted and it is magnetic on the reverse side. Another positive aspect: LED Luc generates very little heat. And the luminaire provides excellent colour reproduction.

LED-Luc 60 is the miniature spot's big brother. Hence, it provides a three times higher power output. Other beneficial features are identical – down to the spherical head magnet, used to position the light beam.

Features

- High flexibility due to a multitude of application options and individual adjustability
- Magnetic base
- For private residences, showrooms, churches, castles, museums, trade fairs, libraries, galleries
- To gently illuminate paintings, works of art, exhibits
- No UV components
- Low heat/thermal load, hence, only very little air-conditioning
- Excellent CRI [CRI > 90]



LED-LUC 60

Sheik Rashid Auditorium,
Dubai

ARCHITECT/LIGHT PLANNER | DISTRIBUTION PARTNER

Arcline Interiors, Dubai | Eros Group, Dubai



LED-LUC 60

Magnetic Spot »L«

GENERAL TECHNICAL SPECIFICATIONS



DIMENSIONS [W X H]	60 x 100 mm	IP RATING	IP44
POWER CONSUMPTION	4–9 W depending on energization 350–700 mA	CERTIFICATES	CE, RoHs
OPERATING VOLTAGE	Low voltage to 48V DC	LUMINAIRE HOUSING WITH BULLET MAGNET	Aluminium natural or black anodised Aluminium vanished white RAL9010
LIGHT BEAM ANGLE	25°/45°/60° freely swivelling on bullet magnet	ATTACHEMENTS [OPTIONAL]	Thread for screwing on honey comb mesh Thread for screwing on tapered
SERVICE LIFE	LED 50,000 hours at 70% of mean luminous flux	CONTROL INTERFACE	Static or digital dimmable converter, DALI
COLOUR TEMPERATURE	White 2,600/3,000/3,500/4,000 Kelvin	WEIGHT	0.3 kg
CRI	CRI > 90	LIGHTING CALCULATION	For EULUM data see www.ado-lights.com
NO. OF LEDS	3		



LIGHT SPREAD | LED-Luc 60

