



sop Architekten, Düsseldorf | die developer, Düsseldorf | Fotografier: Peter von Plogge

LED-AROUND

Standing Luminaire

BASE INFORMATION



LED-Around | Light in all directions

Combining sophistication and efficiency. Upward and downward light radiation. Ensures homogeneous, glare-free illumination. Fully transparent when switched off. LED Around is useful everywhere, in offices and administrative buildings, in show rooms and private residences.

As a freestanding luminaire, LED Around is a true all-rounder: it can provide radiant, glare-free but still subdued lighting. A captivating product – thanks to its minimalist design and high-quality finish.

Features

- For offices, showrooms, hotels, laboratories, shop floors and private residences
- Narrow light colour tolerances
- Direct/indirect light extraction; optional direct light extraction with reflector
- Perfect homogeneous light spread
- Glare-free
- Steplessly dimmable and suitable to VDU workstations



LED-AROUND

Clara + Robert,
Düsseldorf

CLIENT | ARCHITECT
die developer, Düsseldorf | sop slapa oberholz pszczulny architekten, Düsseldorf



LED-AROUND

Standing Luminaire

GENERAL TECHNICAL SPECIFICATIONS



DIMENSIONS [L X W X H]	HEAD 610 x 320 x 20 mm BASE 420 x 320 mm [L x W] TOTAL HEIGHT 1,950 mm	IP RATING	IP20
POWER CONSUMPTION	85 W	LUMINAIRE HOUSING	HEAD: Aluminium natural or black anodised PIPE: Aluminium natural or black anodised BASE PLATE: Aluminium natural or black anodised; weighted down with steel plate black Other colours upon request
LUMINOUS FLUX	Module efficiency 108 lm/W Direct/indirect 4,117 lm/2.745 lm At 100 % direct 6,862 lm Nominal luminous flux 9,150 lm	CONVERTER	Overload protection Overtemperature protection Short-circuit protection Dimming adjustable for DC-mode
OPERATING VOLTAGE	230 V	OPTIONS	Presence detector Cluster switches Daylight sensor
SEVICE LIFE	LED 50.000 hours at 70% of mean luminous flux	WEIGHT	18 kg
COLOUR TEMPERATURE	White 3,000/4,000 Kelvin	LIGHTING CALCULATION	For EULUM data see www.ado-lights.com
CRI	CRI > 85 Narrow colour tolerance MacAdam Step 3		
NORM/PERFORMANCE	UGR < 19 L65 < 1,500 cd/m ² according to EN 12464-1:2011		

LIGHT SPREAD | LED-Around | Standing luminaire

