
LED-HAYAT

Tender

TTC Timmler Technology GmbH
Christian-Schäfer-Straße 8
D-53881 Flamersheim [Cologne/Bonn]
T +49 2255 9212-00
F +49 2255 9212-99
E info@ado-lights.com
I www.ado-lights.com
www.led-luc.com

ADO ®
by TTC Timmler Technology

LED-HAYAT

Recessed/Surface-mounted or Pendant Luminaire



TENDER



LED-HAYAT | PENDANT OR RECESSED/SURFACE-MOUNTED LUMINAIRE

ADO Lights pendant [LHP] or recessed [LHA] luminaire type »LED-Hayat« made of aluminium square profile [50 x 50 mm], surface natural or black anodised – optional powder-coated according to RAL

LED light spot spacing 250 mm [standard] in aluminium profile; round necks with diameter 30 mm centered on a width of 50 mm, therein round plates flush with surface, underneath each 1 LED element, consisting of a high-power LED with high-power lens in heatsink, light beam angle 10°, 25°, 50° or 25°/50° elliptical

LED white 2,600, 3,000, 3,500 or 4,000 Kelvin, low voltage to 48 V DC, 350–400 mA CC, module efficiency 88lm/W, CRI > 90

IP rating IP54, optional IP65

External driver, control facility manual, DALI or DMX

DELIVERY CONTENTS	LED-Hayat Mounting kit: stainless steel cable or surface-mounted installation housing Ballast
DIMENSIONS [L x W x H]	1,400 x 50 x 50 mm 2,800 x 50 x 50 mm
MANUFACTURER	ADO Lights by TTC Timmler Technology GmbH
TYPE DESCRIPTION	LHP »length« »Kelvin« »lens« LHA »length« »Kelvin« »lens«
ORDER UNIT	Piece