
LED-LIGHTLINE

Tender

TTC Timmler Technology GmbH
Christian-Schäfer-Straße 8
D-53881 Flamersheim [Cologne/Bonn]
T +49 2255 9212-00
F +49 2255 9212-99
E info@ado-lights.com
I www.ado-lights.com
www.led-luc.com

ADO ®
by TTC Timmler Technology

LED-LIGHTLINE

Recessed Luminaire

Standard/High-power



TENDER



LED-LIGHTLINE | STANDARD OR HIGH-POWER

ADO Lights luminaire type »LED-LightLine« made of natural anodised aluminium profile 12/30 mm and aluminium mounting profile 15/45 mm

Standard: equipped with SMD-LED white 2,700, 3,000 or 3,500 Kelvin, operating voltage 24 V DC, power consumption 19 W/m

High-power: equipped with SMD-LED white 3,000, 3,500 or 4,500 Kelvin, operating voltage 24 V DC, power consumption 38 W/m

Multicolor: equipped with LED multicolor RGB, operating voltage 24 V DC, power consumption 14 W/m

Opaque polyurethane seal for homogeneous illumination without dark spots at the junction, polyurethane seal conform to RoHS and WEEE, UV resistant, weather resistant

IP rating IP68 | connection cable with plug connection IP67

In combination with ballast compatible to any interface e.g. DMX512, DALI, EIB etc.

Safe to walk-on and roll-over design for vehicles with air-filled tires up to 30 kN according to DIN EN 60598-2-13

Optional: installation housing made of stainless steel to integrate LED-LightLine in different floorings

DELIVERY CONTENTS	LED-LightLine straight version or curved version by definition Mounting profile
DIMENSIONS [W x H]	12 x 30 mm variable length, up to 4 metres in one piece
MANUFACTURER	ADO Lights by TTC Timmler Technology GmbH
TYPE DESCRIPTION	LLE.19 »Kelvin« LLE.38 »Kelvin« LLE.14 RGB
ORDER UNIT	mtr