
LED-LUC 60

Tender

TTC Timmler Technology GmbH
Christian-Schäfer-Straße 8
D-53881 Flamersheim [Cologne/Bonn]
T +49 2255 9212-00
F +49 2255 9212-99
E info@ado-lights.com
I www.ado-lights.com
www.led-luc.com

ADO ®
by TTC Timmler Technology

LED-LUC 60

Magnetic Spot »L«



TENDER



LED-LUC 60 | MAGNETIC SPOT »L«

ADO Lights-LED-MiniSpot type »LED-Luc 60« made of aluminium natural or black anodised or powder-coated according to RAL 9010 white, optional other RAL colours

Flexible mounting options with magnetic base; targeted illumination and free alignment options by the bullet magnet of the minispot; light beam angle 10°, 25° or 50°

LED white 2,600, 3,000, 3,500 or 4,000 Kelvin, CRI > 90, power consumption 4–9 watt depending on energization 350–700 mA (88 lm/W at 350 mA); low voltage to 48V DC

Protection class III, IP rating IP44

Attachments [optional]: AC adapter, dimmable driver, thread for screwing on with anti-glare honey-comb mesh, tapered thread for screwing on, connecting cable, 4-conductor fourfold

DELIVERY CONTENTS	Spot LED-Luc 60
DIMENSIONS [W x H]	60 x 100 mm
MANUFACTURER	ADO Lights by TTC Timmler Technology GmbH
TYPE DESCRIPTION	LLG »Kelvin« »lens«
ORDER UNIT	Piece