
LED-SPACELIGHT

Tender

TTC Timmler Technology GmbH
Christian-Schäfer-Straße 8
D-53881 Flamersheim [Cologne/Bonn]
T +49 2255 9212-00
F +49 2255 9212-99
E info@ado-lights.com
I www.ado-lights.com
www.led-luc.com

ADO ®
by TTC Timmler Technology

LED-SPACELIGHT

Façade and Surface Luminaire



TENDER



LED-SPACELIGHT | FAÇADE/SURFACE LUMINAIRE

ADO Lights luminaire type »LED-Spacelight« as façade and surface luminaire, luminaire housing made of aluminium, anodised or powder-coated according to RAL

Satinised PMMA sheet for homogeneous, glare-free illumination, covering ESG glass optiwhite with passepartout print

LED white 2,700, 3,000, 4,000 or 5,000 Kelvin, CRI > 85, optional LED multicolor RGB, operating voltage 24 V DC

IP rating IP54/65

In combination with ballast compatible to any interface e.g. DMX512, DALI, EIB etc.

Optional: with mounting device for installation at on site construction

DELIVERY CONTENTS	LED-SpaceLight Ballast
DIMENSIONS [L x W]	Light area max. 1.500 x 3.000 mm Set up depth 25–40 mm
MANUFACTURER	ADO Lights by TTC Timmler Technology GmbH
TYPE DESCRIPTION	LSP »length« x »width« »Kelvin«
ORDER UNIT	Piece