

LED-GROUND-LEVEL SPOT

Recessed Floor Luminaire



LED-GROUND-LEVEL SPOT

Recessed Luminaire

BASE INFORMATION



LED-Ground-level spot | Spot on façades

This LED-Ground-level spotlight creates a very positive effect. It can be used to flood façades strikingly with light. Dark outdoor areas are a thing of the past. The LED-Ground-level spot is either buried flush with the ground or it can be visible like an elegant object. Maximum effect but still glare-free illumination: for residential buildings, villas, gardens and castles.

Merkmale

- For private residences, villas, parks, gardens, churches, castles, historic buildings
- Stainless steel housing for exterior use
- Weather-proof
- Glare-free



LED-GROUND-LEVEL SPOT

Recessed Luminaire

ACCENT LIGHTING

Kulturhof, private residence and publishing house Süddeutsche



LED-GROUND-LEVEL SPOT

Recessed Luminaire

BASE INFORMATION AND GENERAL TECHNICAL SPECIFICATIONS



| | | | |
|-------------------------------|--|-----------------------------|---|
| DIMENSIONS [L X B X H] | 150 x 150 x 120 mm | CRI | CRI > 85 |
| POWER CONSUMPTION | MONOCHROME/WHITE: 16 W RGB/MULTICOLOUR: 6 W | CONTROL INTERFACE | With ballast compatible to any interface e.g. DMX512, DALI, EIB etc. |
| LUMINOUS FLUX | Module efficiency 104 lm/W Luminous flux 1,276 lm Nominal luminous flux 1.604 lm | IP RATING | IP67 |
| OPERATING VOLTAGE | 24V DC | CERTIFICATES | CE, RoHs |
| LIGHT BEAM ANGLE | 120° or asymmetrical | LUMINAIRE HOUSING | Stainless steel |
| SERVICE LIFE | LED and EVG 40,000 hours at 70% of mean luminous flux | COVER | VSG-Safety glass, drive-over design for wheel loads up to 1.5 t |
| COLOUR TEMPERATURE | MONOCHROME/WHITE: 2,700/3,000/4,000 Kelvin optional RGB | CONVERTER | Overload protection Overtemperature protection Short-circuit protection |
| | | LIGHTING CALCULATION | For EULUM data see www.ado-lights.com |

LIGHT SPREAD | LED-Ground-level spot

