
LED-AROUND

Tender
Pendant Luminaire

TTC Timmler Technology GmbH
Christian-Schäfer-Straße 8
D-53881 Flamersheim [Cologne/Bonn]
T +49 2255 9212-00
F +49 2255 9212-99
E info@ado-lights.com
I www.ado-lights.com
www.led-luc.com

ADO ®
by TTC Timmler Technology

LED-AROUND

Pendant Luminaire



TENDER



LED-AROUND | FILIGREE PENDANT LUMINAIRE

ADO Lights luminaire type »LED-Around – filigree pendant luminaire« made of aluminium natural or black anodised – optional coated according to RAL

Light output PMMA sheet with microprismatic optic [60% direct, 40% indirect], glare-free, UGR<19, L65 < 1,500 cd/m² according to EN 12464-1:2011

LED white 3,000 or 4,000 Kelvin, power consumption [1,210 mm 90 watt] [1,830 mm 135 watt] [2,430 mm 180 watt], 110 lm/W, narrow colour tolerance MacAdam Step 3

Protection class III, IP rating IP 20

Stainless steel mounting cable, height adjustable 1.5 m and transparent supply line 1.5 m

External power supply with control interface DALI, DSI, switch DIM with memory function and corridor function; optional with housing for power supply made of anodised aluminium

DELIVERY CONTENTS	LED-Around pendant luminaire Power supply 90W, 1,750mA CC [1,830/2.,430 mm 2 pieces each] Mounting kit [stainless steel wire cable incl. mounting material]
DIMENSIONS [L x W x H]	Luminaire [standard] 1,210 x 200 x 20 mm Luminaire [loang] 1,830 x 200 x 20 mm Luminaire [extralong] 2,430 x 200 x 20 mm Lum. housing [opt.] 190 x 140 x 40 mm
MANUFACTURER	ADO Lights by TTC Timmler Technology GmbH
TYPE DESCRIPTION	LAP »length«x»width« »Kelvin«
ORDER UNIT	Piece