
LED-AROUND

Tender
Standing Luminaire

TTC Timmler Technology GmbH
Christian-Schäfer-Straße 8
D-53881 Flamersheim [Cologne/Bonn]
T +49 2255 9212-00
F +49 2255 9212-99
E info@ado-lights.com
I www.ado-lights.com
www.led-luc.com

ADO ®
by TTC Timmler Technology

LED-AROUND

Standing Luminaire



TENDER



LED-AROUND | FILIGREE STANDING LUMINAIRE

ADO Lights luminaire type »LED-Around – filigree standing luminaire« made of aluminium natural or black anodised – optional coated according to RAL

Light output PMMA sheet with microprismatic optic [60% direct, 40% indirect], glare-free, UGR < 19, L65 < 1,500 cd/m² according to EN 12464-1:2011

LED white 3,000 or 4,000 Kelvin, power consumption 85 watt, 108 lm/W, narrow colour tolerance MacAdam Step 3

Protection class III, IP rating IP 20

Internal power supply, On/Off – dimmable – optional with cluster switches [via Zigbee], presence detector and daylight sensor

DELIVERY CONTENTS	LED-Around standing luminaire in 3 parts
DIMENSIONS [L x W x H]	Luminaire head 610 x 320 x 20 mm
	Base plate 420 x 320 x 30 mm
	Pipe [total height] 1.950 mm
MANUFACTURER	ADO Lights by TTC Timmler Technology GmbH
TYPE DESCRIPTION	LAS »Kelvin« 420
ORDER UNIT	Piece