
LED-LINARGO

Tender

TTC Timmler Technology GmbH
Christian-Schäfer-Straße 8
D-53881 Flamersheim [Cologne/Bonn]
T +49 2255 9212-00
F +49 2255 9212-99
E info@ado-lights.com
I www.ado-lights.com
www.led-luc.com

ADO ®
by TTC Timmler Technology

LED-LINARGO

Pendant/Recessed Luminaire



TENDER



LED-LINARGO | MODERN PENDANT/RECESSED LUMINAIRE

ADO Lights recessed or pendant luminaire type »LED-Linargo« made of aluminium, natural or black anodised or powder-coated according to RAL

Opal cover with PMMA for homogeneous illumination

LED white 3,000 or 4,000 Kelvin, at 1,690 mm 51 W [standard], CRI > 84, 143 lm/W, narrow colour tolerance MacAdam Step 3, dimmable with DALI control interface, UGR < 19, L65 < 1.500 cd/m² according to EN 12464-1:2011

IP rating IP40

Cable wire 1.5 m and supply line 1.5 m transparent

Optional for pendant luminaire: separately switchable direct/indirect light, optional emergency light

DELIVERY CONTENTS	LED-Linargo pendant luminaire [LLP] Mounting kit [cable wire incl. mounting material] LED-Linargo recessed luminaire [LLE] Mounting kit [spring clips for mounting]
DIMENSIONS [L x W x H]	Luminaire [standard] 1,690 x 38 x 80 mm Variable length: 570 mm [17W] 1,130 mm [34W] 1,690 mm [51W] 2,250 mm [68W] Special length:. 2,810 mm [85W] 3,370 mm [102W] others upon request
MANUFACTURER	ADO Lights by TTC Timmler Technology GmbH
TYPE DESCRIPTION	Pendant: LLP direct/indirect »length« »Kelvin« Recessed: LLE »length« »Kelvin«
ORDER UNIT	Piece