
LED-QME 625

Tender

TTC Timmler Technology GmbH
Christian-Schäfer-Straße 8
D-53881 Flamersheim [Cologne/Bonn]
T +49 2255 9212-00
F +49 2255 9212-99
E info@ado-lights.com
I www.ado-lights.com
www.led-luc.com

ADO ®
by TTC Timmler Technology

LED-QME 625

Surface-mounted/recessed luminaire,
surface light, square



TENDER



LED-QME 625 | SQUARE SURFACE LUMINAIRE

ADO Lights square surface luminaire type »LED-QME 625« version as LED insert panel with frame made of aluminium powder-coated white

Opal covering with PMMA sheet, satinised for homogeneous and glare-free illumination

LED white 3,000 or 4,000 Kelvin, CRI > 82, power consumption 40W, module efficiency 90 lm/W, luminous flux 3.600 lm

IP rating IP44

Optional: UGR < 19 [glare-free for offices], with mounting or built-in frame for mounting below the ceiling

DELIVERY CONTENTS	LED-QME 625 surface luminaire Ballast
DIMENSIONS [L x W x H]	LED panel 620 x 620 x 15 mm Mounting frame 625 x 625 x 50 mm
MANUFACTURER	ADO Lights by TTC Timmler Technology GmbH
TYPE DESCRIPTION	QME625 »Kelvin«
ORDER UNIT	Piece