
LED-VOUTE

Tender

TTC Timmler Technology GmbH
Christian-Schäfer-Straße 8
D-53881 Flamersheim [Cologne/Bonn]
T +49 2255 9212-00
F +49 2255 9212-99
E info@ado-lights.com
I www.ado-lights.com
www.led-luc.com

ADO ®
by TTC Timmler Technology

LED-VOUTE

Indirect Ambient Lighting



TENDER



LED-VOUTE | COVE LIGHTING

ADO Lights luminaire type »LED-Voute« 19/13 mm with housing made of aluminium, natural anodised

Opaque covering for homogeneous, glare-free illumination without dark spots at the junction, 65 % light transmission

SMD-LED white 2,700, 3,000, 4,000 or 6,000 Kelvin, power consumption 19 W/m or RGB 14 W/m, operating voltage 24 V DC

IP rating IP40

Connection cable with plug connections incl. mounting brackets

In combination with ballast compatible to any interface e.g. DMX512, DALI, EIB etc.

DELIVERY CONTENTS	LED-Voute Ballast Mounting brackets
DIMENSIONS [W x H]	19 x 13 mm variable length, up to 4 metres in one piece
MANUFACTURER	ADO Lights by TTC Timmler Technology GmbH
TYPE DESCRIPTION	LVO.19 »Kelvin« LVO.14 RGB
ORDER UNIT	mtr